



## Continuously Manufactured Sheet Products

**Acrylite<sup>FF</sup>**  
ACRYLIC SHEET



**ACRYLITE<sup>®</sup> FF** acrylic sheet is a continuously manufactured acrylic sheet. It is produced by an innovative process, resulting in a acrylic sheet offering the easy handling and processing of extruded acrylic sheet, along with the high optical characteristics and low stress levels expected of cast products. ACRYLITE FF acrylic sheet carries an exclusive 10-year limited warranty on light transmission.

Acrylic Sheet 48" x 96", 51" x 100", 60" x 96", 72" x 96", 100" x 100", 100" x 125", 100" x 150"

All acrylic sheets are protected with polyethylene film or paper masking.

Thickness .060", .080", .090", .098", .118", .177", .220", .236", .354", .472", .708", .944"

Color: Colorless, Colors, Transparent, Opaque, Translucent

### Applications.

- Skylights
- Signs
- Window Glazing/Frames
- Picture Framing
- Store or P-O-P Displays
- Optical Display

**Weather Resistance:** ACRYLITE FF sheet will withstand exposure to blazing sun, extreme cold, sudden temperature changes, salt water spray, etc. It will not deteriorate after many years of service because of the inherent stability of acrylic resins.

**Chemical Resistance:** ACRYLITE FF sheet has excellent resistance to many chemicals including:

- Solutions of inorganic alkalies such as ammonia
- Dilute acids such as sulfuric acid up to a concentration of 30%
- Aliphatic hydrocarbons such as hexane and VM&P naphtha

**ACRYLITE<sup>®</sup> FF-3** - acrylic sheet picture framing grade acrylic sheet is the highest quality acrylic sheet available for the framing market. Continuously manufactured using a proprietary process, ACRYLITE FF-3 Framing grade sheet is guaranteed to be defect free.

Acrylic Sheet: 48" x 96" Thickness: .060", .080", .090", .098", .118" Color: Clear

**ACRYLITE<sup>®</sup> FF P-99** - acrylic sheet has a matte finish, non glare surface that can be painted or silk screened.

Acrylic Sheet: 48" x 96" Thickness: .060", .080", .098", .118" Color: Clear non glare

**ACRYLITE<sup>®</sup> OP-3** - acrylic sheet filters 98% U.V. light. Its light weight, superior impact resistance, and ease of fabrication, make it an ideal choice for framing articles of value. ACRYLITE OP 3 sheet is also available with a matte finish to reduce glare.

Acrylic Sheet: 48" x 96" Thickness: .098", .118" Color: Clear non glare

**ACRYLITE<sup>®</sup> OP-3 P-99** - acrylic sheet offers UV light filtering and a non-glare surface for picture framing and signage.

Acrylic Sheet: 48" x 96" Thickness: .098" and .118" Color: Clear non glare

**ACRYLITE<sup>®</sup> AR** acrylic sheet has an abrasion resistant coating on one side or both sides to offer optimal protection from surface marring common to public displays. The one sided option provides the protection needed for framing and offers a significant economic benefit. Its chemical resistant coating allows cleaning with alcohol or ammonia based cleaners like Windex window cleaner.

**ACRYLITE<sup>®</sup> AR OP-3** - acrylic sheet offers abrasion and chemical resistance with UV light filtering properties for museums and gallery applications.

Acrylic Sheet: 48" x 96" Thickness: .098", .118" Color: Clear