



Non Glare - Acrylic



LUCITE® Non-Glare

- Excellent glare reducing properties
- Less weight - 50% less than glass
- Shatter resistant - 30 times the strength of single strength glass
- Easy to fabricate - can be cut, routed, drilled, decorated, solvent cemented and thermoformed
- UV protection from fading - filters out up to 87% of harmful UV rays

Product Description:

LUCITE CP Frame Grade is continuously processed in a clean room environment, virtually eliminating internal and external surface imperfections. A fine matte surface reduces reflected glare while maintaining excellent readability.

Applications:

- Picture framing
- Architectural Applications
- Signage

		Size	Pcs/Ctn	Pcs/Bulk
Packaging	Thickness	48" x72"	48" x 96"	60" x 96"
Carton Pack	.060"	6 (P)	-	-
	.080"	-	5 (P)	-
	.093"	-	-	-
	.118"	-	3 (P)	-
	.177"	-	3 (P)	-
Bulk Pack	.060"	100 (PFA) 100 (P)	50 (PFA) 50 (P)	- -
	.080"	- -	100 (PFA) 100 (P)	- -
	.093"	-	100 (PFA) 100 (P)	- -
	.118"	-	80 (PFA) 80 (P)	80 (P) -

(PFA) = Polyfilm smooth side, Adhesive polyfilm Non-Glare side
(P) = Paper Masked