



## Tygon® Beverage Tubing

### Formulation B-44-3

- Taste-free and odor-free
- Non-wetting surface permits thorough cleaning and complete drainage
- Broad chemical resistance to virtually all non-solvent chemicals
- Lightweight and flexible for easy, quick installation
- Meets FDA, 3-A and NSF criteria

This flexible tubing is especially recommended for handling most types of beverages, water, cooking oils, syrups, juices, extracts and preservatives. Excellent for permanent or temporary lines. Can be used in conjunction with rigid piping systems. Maximum recommended operating temperature is 165°F (74°C). Autoclavable. Durometer hardness: Shore A, 63.

I.D. inches	x	O.D. inches	I.D. inches	x	O.D. inches
1/16	x	1/8	7/16	x	11/16
1/16	x	3/16	1/2	x	5/8
3/32	x	5/32	1/2	x	11/16
3/32	x	7/32	1/2	x	3/4
1/8	x	1/4	5/8	x	7/8
5/32	x	7/32	11/16	x	15/16
5/32	x	9/32	3/4	x	1
3/16	x	1/4	7/8	x	1-1/8
3/16	x	5/16	1	x	1-1/4
3/16	x	3/8	1	x	1-3/8
3/16	x	7/16	1	x	1-1/2
1/4	x	5/16	1-1/4	x	1-1/2
1/4	x	3/8	1-1/4	x	1-3/4
1/4	x	7/16	1-1/2	x	1-7/8
1/4	x	1/2	1-1/2	x	2
5/16	x	7/16	1-3/4	x	2-1/4
5/16	x	1/2	2	x	2-1/2
5/16	x	9/16	2	x	3
3/8	x	1/2	2-1/4	x	2-3/4
3/8	x	9/16	3	x	3-1/2
3/8	x	5/8			



The most widely specified clear, flexible tubing, Tygon® Beverage Tubing is frequently chosen for its taste and odor-free characteristics.

