



## Tygon® Food, Milk & Dairy Products Tubing

### Formulation B-44-4X

- Smooth, non-porous bore will not trap particulates or promote bacterial growth
- Compatible with foods containing a high oil content
- Resistant to harsh alkaline cleaners and sanitizers
- Excellent alternative to rigid piping systems
- Meets FDA, 3-A and NSF criteria

FDA compliant. Meets all criteria in the 3-A Plastics Standard for handling milk and milk products and is NSF listed Standard 51. Clear, lightweight tubing is nontoxic, highly resistant to alkaline cleaners and unaffected by sanitizers. Dense bore is smoother than most stainless steels. Won't trap bacteria-harboring particles. Excellent wetting properties facilitate complete drainage and permit simple flush cleaning. Maximum recommended operating temperature is 165°F (74°C). Durometer hardness: Shore A, 65.

I.D. inches	x	O.D. inches	I.D. inches	x	O.D. inches
1/32	x	3/32	1/2	x	5/8
1/16	x	1/8	1/2	x	3/4
1/16	x	3/16	1/2	x	13/16
3/32	x	5/32	9/16	x	3/4
3/32	x	7/32	5/8	x	13/16
1/8	x	3/16	5/8	x	7/8
1/8	x	1/4	5/8	x	15/16
5/32	x	7/32	3/4	x	1
5/32	x	9/32	3/4	x	1-1/16
3/16	x	1/4	3/4	x	1-1/8
3/16	x	5/16	3/4	x	1-1/4
3/16	x	3/8	7/8	x	1-1/8
3/16	x	7/16	1	x	1-1/4
1/4	x	5/16	1	x	1-5/16
1/4	x	3/8	1	x	1-3/8
1/4	x	7/16	1	x	1-1/2
1/4	x	1/2	1-1/8	x	1-3/8
5/16	x	7/16	1-1/4	x	1-1/2
5/16	x	1/2	1-1/4	x	1-5/8
5/16	x	9/16	1-1/4	x	1-3/4
5/16	x	5/8	1-1/2	x	1-7/8
3/8	x	1/2	1-1/2	x	2
3/8	x	9/16	1-3/4	x	2-1/4
3/8	x	5/8	2	x	2-1/2
7/16	x	9/16	2	x	2-3/4
7/16	x	5/8	2	x	3



With its smooth, non-porous bore, Tygon® Food, Milk and Dairy Tubing helps ensure a bacterial-free fluid path in a wide variety of food processing applications.



Ask about standard 20' and 100' lengths.